

2 Way Outdoor Multitaps 750 MHz



Features:

- 5 MHz to 750 MHz bandwidth
- 360 aluminum alloy housing with double polyurethane coating
- Neoprene weather gasket
- RFI gasket
- Epoxy sealed "F" ports
- Nickel plated brass "F" ports machine pressed into faceplate
- Printed circuit board
- 2/4 port faceplates are interchangeable
- Suitable for aerial or pedestal installation
- Rotational seizure mechanism for easy installation

Specifications:

	5-10 MHz	11-20 MHz	21-400 MHz	401-500 MHz	501-600 MHz	601-750 MHz
Isolation(dB) tap-to-tap	18	23	28	28	28	25
Return Loss (In/Out/Tap)	15	18	20	20	18	18
Tap loss tolerance	±1.5	±1.5	±1.5	±1.5	±1.5	±1.7
Power Passing	7.0 Amps AC/DC					

PDI Part No.	Insertion Loss (dB)						
	5-50 MHz	51-300 MHz	301-400 MHz	401-500 MHz	501-600 MHz	601-700 MHz	701-750 MHz
PDI 2/04	T	T	T	T	T	T	T
PDI 2/08	3.2	3.1	3.2	3.5	3.7	3.8	4.2
PDI 2/11	1.4	1.4	1.6	1.9	2.0	2.4	3.0
PDI 2/14	1.2	1.1	1.3	1.4	1.6	1.8	2.0
PDI 2/17	0.7	0.7	0.8	0.9	1.2	1.2	1.4
PDI 2/20	0.6	0.6	0.7	0.8	1.1	1.1	1.3
PDI 2/23	0.5	0.4	0.6	0.7	0.9	1.0	1.3
PDI 2/26	0.5	0.4	0.6	0.7	0.9	1.0	1.3
PDI 2/29	0.5	0.4	0.6	0.7	0.9	1.0	1.3
PDI 2/32	0.5	0.4	0.6	0.7	0.9	1.0	1.3
PDI 2/35	0.5	0.4	0.6	0.7	0.9	1.0	1.3
	Out-To-Tap Isolation (dB)						
	5-50 MHz	51-300 MHz	301-400 MHz	401-500 MHz	501-600 MHz	601-700 MHz	701-750 MHz
PDI 2/04	T	T	T	T	T	T	T
PDI 2/08	18	23	23	22	21	21	19
PDI 2/11	18	23	23	22	21	21	19
PDI 2/14	20	23	21	20	20	20	19
PDI 2/17	30	30	30	30	30	30	28
PDI 2/20	30	30	30	30	27	27	25
PDI 2/23	35	35	33	33	32	32	28
PDI 2/26	38	35	34	33	30	30	26
PDI 2/29	40	42	42	40	39	39	30
PDI 2/32	42	44	44	42	41	41	32
PDI 2/35	44	45	45	44	43	43	32

600 MHz ALSO AVAILABLE