

4 Way Outdoor Multitaps 750 MHz



- 5 MHz to 750 MHz bandwidth
- 360 aluminum alloy housing with double polyurethane coating
- Neoprene weather gasket
- RFI gasket
- Epoxy sealed "F" ports
- Nickel plated brass "F" ports machine pressed into faceplate
- Printed circuit board
- 2/4 port faceplates are interchangeable
- Suitable for aerial or pedestal installation
- Rotational seizure mechanism for easy installation

Specifications:

	5-10 MHz	11-20 MHz	21-40 MHz	401-500 MHz	501-600 MHz	601-750 MHz
Isolation(dB) tap-to-tap	18	23	28	28	28	25
Return Loss (In/Out/Tap)	15	18	20	20	18	18
Tap loss tolerance	+1.5	+1.5	+1.5	+1.5	+1.5	+1.7
Power Passing	7.0 Amps AC/DC					

PDI Part No.	Insertion Loss (dB)						
	5-50 MHz	51-300 MHz	301-400 MHz	401-500 MHz	501-600 MHz	601-700 MHz	701-750 MHz
PDI 4/04	n/a	n/a	n/a	n/a	n/a	n/a	n/a
PDI 4/08	T	T	T	T	T	T	T
PDI 4/11	3.2	3.0	3.2	3.4	3.6	3.7	4.0
PDI 4/14	1.7	1.6	1.8	2.0	2.1	2.4	2.9
PDI 4/17	1.0	0.9	1.2	1.3	1.4	1.6	2.0
PDI 4/20	0.7	0.7	0.8	1.0	1.1	1.2	1.5
PDI 4/23	0.6	0.6	0.7	0.8	1.0	1.1	1.3
PDI 4/26	0.5	0.4	0.6	0.7	0.8	0.9	1.1
PDI 4/29	0.5	0.4	0.6	0.7	0.8	0.9	1.1
PDI 4/32	0.5	0.4	0.6	0.7	0.8	0.9	1.1
PDI 4/35	0.5	0.4	0.6	0.7	0.8	0.9	1.1

PDI Part No.	Out-To-Tap Isolation (dB)						
	5-50 MHz	51-300 MHz	301-400 MHz	401-500 MHz	501-600 MHz	601-700 MHz	701-750 MHz
PDI 4/04	n/a	n/a	n/a	n/a	n/a	n/a	n/a
PDI 4/08	T	T	T	T	T	T	T
PDI 4/11	18	23	23	22	21	21	19
PDI 4/14	20	20	21	20	20	20	19
PDI 4/17	26	26	23	23	21	20	19
PDI 4/20	35	35	35	30	27	27	25
PDI 4/23	35	35	33	33	32	32	28
PDI 4/26	38	35	34	33	30	30	26
PDI 4/29	40	42	42	40	39	39	30
PDI 4/32	42	44	44	42	41	41	32
PDI 4/35	44	45	45	44	43	43	32