

8 Way Outdoor Multitaps 1 GHz



Features:

- 5 MHz to 1 GHz bandwidth
- 360 aluminum alloy housing with double polyurethane coating
- Neoprene weather gasket
- RFI gasket
- Epoxy sealed "F" ports
- Nickel plated brass "F" ports machine pressed into faceplate
- Printed circuit board
- Suitable for aerial or pedestal installation
- Rotational seizure mechanism for easy installation

Specifications:

	5-10 MHz	11-20 MHz	21-400 MHz	401-500 MHz	501-600 MHz	601-900 MHz	901-1000 MHz
Isolation(dB) tap-to-tap	18	23	25	25	23	21	19
Return Loss (In/Out/Tap)	15	18	20	18	17	16	16
Tap loss tolerance	+1.0	+1.0	+1.0	+1.0	+1.3	+1.7	+2.0
Power Passing	7.0 Amps AC/DC						

PDI Part No.	Insertion Loss (dB)									
	5-50 MHz	51-300 MHz	301-400 MHz	401-500 MHz	501-600 MHz	601-700 MHz	701-800 MHz	801-900 MHz	901-1000 MHz	
PDI 8/08 1GHz	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	
PDI 8/11 1GHz	T	T	T	T	T	T	T	T	T	
PDI 8/14 1GHz	3.2	3.6	3.7	3.7	3.9	4.2	4.3	4.2	4.2	
PDI 8/17 1GHz	1.5	1.6	1.7	2.0	2.0	2.3	2.3	2.4	2.7	
PDI 8/20 1GHz	1.1	1.0	1.0	1.2	1.5	1.4	1.7	1.9	2.4	
PDI 8/23 1GHz	0.8	0.7	0.7	0.9	1.2	1.0	1.1	1.2	1.4	
PDI 8/26 1GHz	0.8	0.7	0.7	0.9	1.2	1.0	1.0	1.1	1.2	
PDI 8/29 1GHz	0.5	0.5	0.5	0.8	1.0	0.8	0.9	0.9	1.0	
PDI 8/32 1GHz	0.5	0.5	0.5	0.6	0.8	0.7	0.8	0.8	0.8	
PDI 8/35 1GHz	0.5	0.5	0.5	0.6	0.8	0.9	0.9	0.9	0.9	
PDI Part No.	Out-To-Tap Isolation (dB)									
	5-50 MHz	51-300 MHz	301-400 MHz	401-500 MHz	501-600 MHz	601-700 MHz	701-800 MHz	801-900 MHz	901-1000 MHz	
PDI 8/04 1GHz	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	
PDI 8/08 1GHz	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	
PDI 8/11 1GHz	T	T	T	T	T	T	T	T	T	
PDI 8/14 1GHz	18	25	25	25	23	22	20	20	18	
PDI 8/17 1GHz	18	20	23	23	21	20	19	19	18	
PDI 8/20 1GHz	26	26	23	21	20	20	19	19	18	
PDI 8/23 1GHz	35	35	33	33	32	32	28	28	27	
PDI 8/26 1GHz	35	35	34	33	30	30	26	26	25	
PDI 8/29 1GHz	38	40	35	34	33	33	30	30	27	
PDI 8/32 1GHz	40	42	42	42	41	41	32	32	31	
PDI 8/35 1GHz	42	43	44	44	43	43	32	32	32	

Product specifications and feature may have changed, call for details