

8 Way Outdoor Multitaps 750 MHz



- 5 MHz to 750 MHz bandwidth
- 360 aluminum alloy housing with double polyurethane coating
- Neoprene weather gasket
- RFI gasket
- Epoxy sealed "F" ports
- Nickel plated brass "F" ports machine pressed into faceplate
- Printed circuit board
- 2/4 port faceplates are interchangeable
- Suitable for aerial or pedestal installation
- Rotational seizure mechanism for easy installation

Specifications:

	5-10 MHz	11-20 MHz	21-400 MHz	401-500 MHz	501-600 MHz	601-750 MHz
Isolation(dB) tap-to-tap	18	23	28	28	28	25
Return Loss (In/Out/Tap)	15	18	20	20	18	18
Tap loss tolerance	±1.5	±1.5	±1.5	±1.5	±1.5	±1.7
Power Passing	7.0 Amps AC/DC					

PDI Part No.	Insertion Loss (dB)						
	5-50 MHz	51-300 MHz	301-400 MHz	401-500 MHz	501-600 MHz	601-700 MHz	701-750 MHz
PDI 8/04	n/a	n/a	n/a	n/a	n/a	n/a	n/a
PDI 8/08	n/a	n/a	n/a	n/a	n/a	n/a	n/a
PDI 8/11	T	T	T	T	T	T	T
PDI 8/14	3.5	3.5	3.6	3.9	3.9	4.1	4.2
PDI 8/17	1.7	1.6	1.9	2.0	2.2	2.4	3.0
PDI 8/20	1.2	1.1	1.3	1.4	1.5	1.7	2.1
PDI 8/23	0.9	0.9	1.0	1.2	1.3	1.4	1.7
PDI 8/26	0.8	0.7	0.9	1.0	1.0	1.1	1.4
PDI 8/29	0.7	0.6	0.8	0.9	0.9	1.0	1.3
PDI 8/32	0.7	0.6	0.8	0.9	0.9	1.0	1.3
PDI 8/35	0.7	0.6	0.8	0.9	0.9	1.0	1.3
	Out-To-Tap Isolation (dB)						
	5-50 MHz	51-300 MHz	301-400 MHz	401-500 MHz	501-600 MHz	601-700 MHz	701-750 MHz
PDI 8/04	n/a	n/a	n/a	n/a	n/a	n/a	n/a
PDI 8/08	n/a	n/a	n/a	n/a	n/a	n/a	n/a
PDI 8/11	T	T	T	T	T	T	T
PDI 8/14	18	25	25	25	23	22	20
PDI 8/17	18	20	23	23	21	20	19
PDI 8/20	26	26	23	21	20	20	19
PDI 8/23	35	35	33	33	32	32	28
PDI 8/26	35	35	34	33	30	30	26
PDI 8/29	38	40	35	34	33	33	30
PDI 8/32	40	42	42	42	41	41	32
PDI 8/35	42	43	44	44	43	43	32